

SOLVENT BACKLIT 200 GLOSSY

(SO650)


Details

- Translucent polyester backlit film designed for excellent image quality graphic art applications.
- Vivid colors with high gloss and outstanding image resolution with or without light.
- Easy to install due to the rigid and flat substrate.
- Excellent scratch resistance and waterproof with advanced coating.



Profiled only

Specifications

Length (ft)	100	Width (inch)	36"/54"/60"/87"
Weight (gsm)	275	Coating	Resin
Caliper (mil)	8.2	Base Material	PET
Inner Core (inch)	3	Printer	
Surface	Glossy		

KEY FEATURES

- High Contrast
- High Image Density
- Easy To Install
- Glossy Coating surface

Application

- Lightbox Graphic, Backlit Trade Show Display, Department Store Display, Luminous Advertising Surface, Bus Shelter & Metro Illuminated Signage

General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional.
- Storage : Recommended to store in closed original packaging in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment.
(Humidity 35~65% RH)
- Shelf Life : One year stored in original packaging at recommended temperature.
(Coating warranty guaranteed for 6 months from date of purchase)

How to buy :

- Please call 1-470-359-2111 to place an order or visit www.naturamedia.us for additional information.
- **ICC Profiles are available** by calling the above number.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.