

## UV HEAT REJECTION WINDOW SR

## UHR80SR


### Details

- Heat Rejection 65% (IR reduced 86%) Clear film for décor with sunlight exposed windows
- UV Rejection (99%) to prevent Yellowing of indoor furnishing and skin protection
- Optically Clear Polyester film, Scratch Resistant Treated for easy installation and cleaning
- Permanent Adhesive, no residue upon removal
- UV curable printable

#### \* Installation Guides

Handle with gloves to avoid marks during printing. Not suitable for uneven surfaces.  
 Best for indoor applications (Reverse Printing)  
 Wet mount recommended for larger applications.  
 Clean the mounting surface prior to applying this film

### Specifications

Length (ft)	100	Width (inch)	60"
Weight (gsm)	125	Coating	Resin
Caliper (mil)	4	Base Material	PET
Inner Core (inch)	3" Plastic	Printer	
Surface	Clear	Adhesion at 180', gf/inch	1500 ≤

### KEY FEATURES

Heat block for comfort and energy saving  
 UV block for skin and yellowing protection  
 Optically Clear, Scratch Resistant Treated  
 Permanent adhesive, no residue upon removal  
 UV Curable Printable

### Application

- Retail window advertisements, indoor window advertisements, retail identification signs and residential interiors
- Architectural window decorations, flat surface glass and plastic (acrylic), various window graphics
- Show windows, windows with sunlight exposure

### General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional
- Storage : Recommended to store in closed original packing in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment.  
 (Humidity 35 ~ 65% RH)
- Shelf Life : One year, stored in original packing at recommended temperature  
 (Coating warranty guaranteed for 6 months from date of purchase)

### How to buy :

- Please call 1-470-359-2111 to place an order or visit [www.naturamedia.us](http://www.naturamedia.us) for additional information.
- **ICC Profiles are available** by calling the above number.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.  
 All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.