

## MICRO-TAC AIRFREE WHITE FILM

(WF200)

### Details

- Air free and Satin surface polypropylene film
- Micro-tac adhesive with 100% bubble-free application and residue-free removal on glass
- Eco-solvent, Solvent, UV, Latex ink compatible
- High opacity version & Anti-scratch surface available

#### \* Installation Guides

- Recommend to test a sample prior to full application
- For HP Latex printers use polypropylene media setting
- Recommended for indoor use
- Clean the mounting surface prior to applying this film

### Specifications

Length (ft)	100	Width (inch)	50",54"
Weight (gsm)	300	Coating	Resin
Caliper (mil)	13.2	Base Material	Polypropylene
Inner Core (inch)	3	Printer	E S L Uv
Surface	Satin	Adhesion at	20min 50 ≥
Min. Application	+ 40°F ( 4 °C )	180° gf/25mm	24 hr 100 ≥

### KEY FEATURES

- Air free liner with micro tac adhesive
- Satin finish with PVC free top coating
- Easy to install & reposition
- High quality image & resolution

### Application

- Architectural window decorations, flat surface glass and plastic (acrylic), window graphics, label and decals  
retail aisle banners

### General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional
- Storage : Recommended to store in closed original packing in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment.  
(Humidity 35 ~ 65% RH)
- Shelf Life : One year, stored in original packing at recommended temperature  
(Coating warranty guaranteed for 6 months from date of purchase)

### How to buy :

- Please call 1-470-359-2111 to place an order or visit [www.naturamedia.us](http://www.naturamedia.us) for additional information.
- **ICC Profiles are available** by calling the above number.

[www.naturamedia.us](http://www.naturamedia.us)

1505 Pavilion Place - Suite D, Norcross GA 30093

Tel 470-359-2111  
Fax 470-359-2199